Pharmacy Plus Bluetooth Enabled Refrigerator

47L Pharmacy Plus Upright Fridge with Solid Door

GDMAcode PPSR47BT-UK

SKU code 444411305









Key features

- ✓ Local monitoring and alarm history via Bluetooth
- ✓ Power failure alarm with backup battery powered recording
- √ Solid and glass door options
- ✓ Intelligent fan management system for enhanced performance











Bluetooth Connected Controller

Local temperature monitoring and alarm history via Bluetooth connectivity. Power failure alarm with battery back-up, providing continuous temperature monitoring in the event of power outage.

Lec Medical Smartphone App

Contactless local monitoring of air and load temperatures via smart phone app. Downloadable temperature report and alarm history.

Intelligent Fan Management

Smart fan optimisation aides in temperature stability following door openings, minimising fan activity when door is open to reduce the rate of temperature increase.

Dual Probe Temperature Monitoring

Our dual probe system offers greater temperature accuracy within your appliance, simultaneously measuring both air and product temperatures.

Flexible Internal Storage

Multiple shelf locations provides flexible storage solutions.



Specification. 1721 Harrings Flas opright Flage with Solid Be	
Gross Capacity (litres)	47L
Net Capacity (litres)	30L
Unit External Width (mm)	475mm
Unit External Depth (mm)	445mm
Unit External Height (mm)	565mm
Product Weight (kg)	17.5Kg
Packed Width (mm)	490mm
Packed Depth (mm)	530mm
Packed Height (mm)	620mm
Packed Weight (kg)	21.5Kg
Country of Origin	UK
Internal Dimensions (mm) (WxDxH)	403mm x 354mm x 425mm
Temperature Range	+2°C to +8°C
Colour	White/Green
External Finish	Painted Steel
Internal Finish	HIPS*
Type of plastic	SRL800 (HIPS/ABS mix)
Door Finish	Painted Steel / Solid
Door Type	Solid
Door Style	Hinged, Reversible
Door Liner	Flat
Number of Door Trays	n/a
Number of Door Tray Positions	n/a
Door Open Depth (mm)	905mm
Replacement Door Seal	No
Open Door Sensor	Yes
Lock	Yes, 2 Keys
Adjustable Feet (number & position)	2 adjustable (front)
Porthole	Yes
Porthole Size	16mm
	Rear LH Corner
Porthole Location Townsertus Display on Bonel	
Temperature Display on Panel	Yes
Temperature Alarm	Yes
Remote Alarm Contacts	Yes
Audible Alarms	Yes
Visual Alarms	Yes
Number of Shelves/Drawers	1
Number of Shelf Positions	3
Shelf Size (mm) (WxDxH)	416mm x 200mm x 6mm
Shelf Material	Polythene Coated Wire
Drawer Size (mm) (WxDxH)	n/a
Drawer Material	n/a
Number of Baskets	1
Basket Material	Polythene Coated Wire
Basket Size (mm) (WxDxH)	396mm x 165mm x 150mm
Interior Light	Yes
Light Type	LED
Light Activation	Door Switch / Controller
Fan	
	Yes - Axial
Spark Free	Yes - Axial No
Spark Free Defrost setting	Yes - Axial No Auto (Off Cycle)
Spark Free Defrost setting Controller Type	Yes - Axial No Auto (Off Cycle) Digital BT, External
Spark Free Defrost setting Controller Type Battery Back Up/Hours	Yes - Axial No Auto (Off Cycle) Digital BT, External No
Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth	Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes
Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth NFC	Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes Yes
Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth NFC WIFI	Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes Yes No
Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth NFC	Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes Yes No 2
Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth NFC WIFI	Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes Yes No 2 Air & Load (Glycol Solution)
Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth NFC WIFI Number of Probes	Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes Yes No 2 Air & Load (Glycol Solution) 10°C to 32°C
Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth NFC WIFI Number of Probes Probe Type	Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes Yes No 2 Air & Load (Glycol Solution)
Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth NFC WIFI Number of Probes Probe Type Ambient Temperature Range	Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes Yes No 2 Air & Load (Glycol Solution) 10°C to 32°C
Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth NFC WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type CFC Free HFC Free	Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes Yes No 2 Air & Load (Glycol Solution) 10°C to 32°C R600a
Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth NFC WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type CFC Free	Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes Yes No 2 Air & Load (Glycol Solution) 10°C to 32°C R600a Yes
Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth NFC WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type CFC Free HFC Free	Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes Yes No 2 Air & Load (Glycol Solution) 10°C to 32°C R600a Yes Yes Yes Yes Ro
Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth NFC WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type CFC Free HFC Free HCFC Free	Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes Yes No 2 Air & Load (Glycol Solution) 10°C to 32°C R600a Yes Yes Yes Yes Yes Yes
Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth NFC WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type CFC Free HFC Free HCFC Free Ammonia Free	Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes Yes Yes No 2 Air & Load (Glycol Solution) 10°C to 32°C R600a Yes Yes Yes Yes Yes Yes Yes Ye
Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth NFC WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type CFC Free HFC Free HCFC Free Ammonia Free UK 3 Pin Plug	Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes Yes Yes No 2 Air & Load (Glycol Solution) 10°C to 32°C R600a Yes Yes Yes Yes Yes Yes Yes Ye
Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth NFC WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type CFC Free HFC Free HCFC Free Ammonia Free UK 3 Pin Plug Other Plug Types Available	Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes Yes Yes No 2 Air & Load (Glycol Solution) 10°C to 32°C R600a Yes Yes Yes Yes Yes Yes Yes Ye
Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth NFC WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type CFC Free HFC Free HFC Free HCFC Free Ammonia Free UK 3 Pin Plug Other Plug Types Available Voltage Supply	Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes Yes Yes No 2 Air & Load (Glycol Solution) 10°C to 32°C R600a Yes
Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth NFC WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type CFC Free HFC Free HFC Free HCFC Free Ammonia Free UK 3 Pin Plug Other Plug Types Available Voltage Supply Insulation Thickness (mm)	Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes Yes Yes No 2 Air & Load (Glycol Solution) 10°C to 32°C R600a Yes
Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth NFC WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type CFC Free HFC Free HFC Free HCFC Free Ammonia Free UK 3 Pin Plug Other Plug Types Available Voltage Supply Insulation Thickness (mm) Insulation Type	Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes Yes Yes No 2 Air & Load (Glycol Solution) 10°C to 32°C R600a Yes
Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth NFC WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type CFC Free HFC Free HFC Free HCFC Free UK 3 Pin Plug Other Plug Types Available Voltage Supply Insulation Thickness (mm) Insulation Type Blowing Agent	Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes Yes Yes No 2 Air & Load (Glycol Solution) 10°C to 32°C R600a Yes
Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth NFC WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type CFC Free HFC Free HFC Free UK 3 Pin Plug Other Plug Types Available Voltage Supply Insulation Thickness (mm) Insulation Type Blowing Agent Anti Microbial Handle Wall Brackets	Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes Yes Yes No 2 Air & Load (Glycol Solution) 10°C to 32°C R600a Yes
Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth NFC WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type CFC Free HFC Free HFC Free UK 3 Pin Plug Other Plug Types Available Voltage Supply Insulation Thickness (mm) Insulation Type Blowing Agent Anti Microbial Handle Wall Brackets Optional Drawer System	Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes Yes Yes No 2 Air & Load (Glycol Solution) 10°C to 32°C R600a Yes
Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth NFC WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type CFC Free HFC Free HFC Free UK 3 Pin Plug Other Plug Types Available Voltage Supply Insulation Thickness (mm) Insulation Type Blowing Agent Anti Microbial Handle Wall Brackets	Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes Yes Yes No 2 Air & Load (Glycol Solution) 10°C to 32°C R600a Yes

