



# Undermounted Counters With Drawers

SPU201-2D / SPU201-4D / SPU303-6D

**1** Year Parts & Labour Warranty

**2-3** Working Days Delivery

**UK** Service Support



The Sterling Pro Cobus SPU201-2D (x2 drawers), SPU201-4D (x4 drawers) and SPU303-6D (x6 drawers) refrigerated undermounted counter range is designed to keep your fresh ingredients safely chilled without costing the earth. The combination of drawers and doors gives extra flexibility to your storage capacity. Using the most efficient environmentally friendly refrigerant this range will minimise running costs while the catering-grade stainless steel construction allows for hygienic food preparation.

Model	Doors	Drawers	Gross & Nett Capacity		Temperature Range	Energy Consumption	Energy Rating	Dimensions (mm)		
<b>SPU201-2D</b>	x1	x2	230 ltrs	198 ltrs	+2°C to +8°C	830 kWh/year	C	W900	D700	H850
<b>SPU201-4D</b>	x0	x4	220 ltrs	198 ltrs	+2°C to +8°C	830 kWh/year	C	W900	D700	H850
<b>SPU303-6D</b>	x0	x6	368 ltrs	297 ltrs	+2°C to +8°C	1294 kWh/year	D	W1365	D700	H850



# Undermounted Counters With Drawers

**SPU201-2D / SPU201-4D / SPU303-6D**



Range Specifications			
	SPU201-2D Counter	SPU201-4D Counter	SPU303-6D Counter
GTIN Code	5060750321744	5060750321751	5060750322161
Dimensions	W900 x D700 x H850mm	W900 x D700 x H850mm	W1365 x D700 x H850mm
Internal Dimensions	W830 x D595 x H455mm	W830 x D595 x H455mm	W1295 x D595 x H455mm
Packed Dimensions	W950 x D750 x H910mm	W950 x D750 x H910mm	W1410 x D750 x H910mm
Gross/Nett Capacity	230 Litres / 198 Litres	220 Litres / 198 Litres	368 Litres / 297 Litres
Doors	1	0	0
Drawers	2	4	6
Shelves Supplied	1	0	0
Exterior Finish	SS201 Stainless Steel	SS201 Stainless Steel	SS201 Stainless Steel
Temperature Range	+2°C to +8°C	+2°C to +8°C	+2°C to +8°C
Max Ambient	32°C	32°C	32°C
Refrigerant	R600	R600	R290
Insulation Thickness	35mm	35mm	35mm
Nett Weight	80kg	80kg	98kg
Energy Rating	C	C	D
Climate Class	4	4	4
Energy Consumption	830 kWh/yr / 2.274 kWh/day	830 kWh/yr / 2.274 kWh/day	1294 kWh/yr / 3.544 kWh/day
Power Supply	13 amp single phase plug	13 amp single phase plug	13 amp single phase plug
Voltage	220-240V/50HZ	220-240V/50HZ	220-240V/50HZ
Cooling System	Static cooling with fan	Static cooling with fan	Static cooling with fan
Defrost Type	Automatic	Automatic	Automatic
Reversible Doors	No	No	No
Lighting	No	No	No
Lockable	No	No	No
Castors	No	No	No
Frost Free	No	No	No
Charging Volume	65g	65g	90g
Compressor Code	LK118CY1	LK118CY1	L58CU1
Compressor Brand	Donper	Donper	Donper