# **SILVERLINK 600**



BM6AW - Lincat Silverlink 600 Electric Counter-top Bain Marie - Wet Heat -Gastronorms - Base + Dish Pack - W 600 mm -2.0 kW The Silverlink 600 Electric Wet Heat Bain Marie safely holds sauces, soups, gravy and precooked foods for up to two hours at the ideal serving temperature

- Wet heat bain marie
- Ideal for holding foods for up to 2 hours at serving temperature
- 4x 1/4 and 1x 1/2 150mm deep gastronorms with lids are included
- This wet unit can also be used as a dry bain marie
- Plug and play for an easy installation
- Perfect for safely holding sauces, gravy & precooked foods
- Adjustable temperature control

2.000

8.7

230

### **Specifications**

Summary  Brand Lincat Total Power kW 2.00 Range Silverlink 600 IP Rating Power Type Liectric Unit Type Counter-top Available in UK Only UK Warranty Export Warranty Contact your local dealer GTIN  Capacity  Capacity  Capacity  Drain Location Pot Type Gastronorm Type of Heat  Wet  Weights and Dimensions  Summary  Power and Performance  Total Power kW 2.00 Requires Installation Pating Total Power kW 2.00 Requires Installation No UR Warnanty Requires Electrical Supply Yes Unit Meight Kg No Requires Hardwiring No	Specifications			
Range Silverlink 600 IP Rating IP 33 Power Type Electric Temperature Control Mechanical Unit Type Counter-top Available in UK Only No UK Warranty 2 Years Parts and Labour Warranty Export Warranty Contact your local dealer GTIN 5056105100515  Key Specifications Front-mounted Gastronorm Type Gastronorm Type of Heat Wet  Weights and Dimensions Supply Connections  Page 1 Supply Connections Pequipment (External) mm 600 Requires Electrical Supply Yes UK 3 Pin Plug Yes	Summary		Power and Performance	
Power Type       Electric       Temperature Control       Mechanical         Unit Type       Counter-top       Available in UK Only       No         UK Warranty       2 Years Parts and Labour Warranty       Export Warranty       Contact your local dealer         GTIN       5056105100515       Capacity         Key Specifications        Front-mounted       Gastronorm Capacity       1x GN1/2; 4x GN1/4         Pot Type       Gastronorm       Wet         Supply Connections         Weights and Dimensions       Supply Connections         Unit Height (External) mm       290       Requires Installation       No         Unit Width (External) mm       600       Requires Electrical Supply       Yes         Unit Depth (External) mm       600       UK 3 Pin Plug       Yes	Brand	Lincat	Total Power kW	2.00
Unit Type	Range	Silverlink 600	IP Rating	IP33
Available in UK Only UK Warranty Export Warranty GTIN  Contact your local dealer 5056105100515   Capacity  Drain Location Pot Type Type of Heat  Wet  Wet  Wet  Wet  Castronorm  Supply Connections  Supply Connections  Capacity  Requires Installation No Unit Width (External) mm 600 Requires Electrical Supply UK 3 Pin Plug Yes  Unit Depth (External) mm 600 UK 3 Pin Plug Yes	Power Type	Electric	Temperature Control	Mechanical
UK Warranty Export Warranty GTIN  Contact your local dealer GTIN  Capacity  Capacity  Capacity  Drain Location Pot Type Type of Heat  Wet  Wet  Wet  Wet  Capacity  Capacity  Capacity  Capacity  Capacity  Capacity  Capacity  Capacity  Capacity  Supply Connections  Capacity  No  No  No  Unit Height (External) mm Unit Width (External) mm Onlit Width (External) mm Onlit Width (External) mm Onlit Depth (Extern	Unit Type	Counter-top		
Export Warranty GTIN  Contact your local dealer 5056105100515  Key Specifications  Capacity  Pot Type Type of Heat  Wet  Weights and Dimensions  Capacity  Supply Connections  Requires Installation No Unit Width (External) mm No Unit Width (External) mm No Hold Sold	Available in UK Only	No		
GTIN       5056105100515         Key Specifications       Capacity         Drain Location Pot Type Type Of Heat       Front-mounted Gastronorm       Gastronorm Capacity       1x GN1/2; 4x GN1/4         Weights and Dimensions         Supply Connections         Unit Height (External) mm       290       Requires Installation Requires Electrical Supply Yes       No         Unit Width (External) mm       600       Requires Electrical Supply Yes         Unit Depth (External) mm       600       UK 3 Pin Plug       Yes	UK Warranty	2 Years Parts and Labour Warranty		
Key Specifications  Capacity  Drain Location Pot Type Gastronorm Type of Heat  Weights and Dimensions  Unit Height (External) mm 290 Unit Width (External) mm 800 Requires Electrical Supply UK 3 Pin Plug Yes	Export Warranty	Contact your local dealer		
Drain Location Front-mounted Gastronorm Capacity 1x GN1/2; 4x GN1/4 Pot Type Gastronorm Type of Heat Wet  Weights and Dimensions  Unit Height (External) mm 290 Unit Width (External) mm 600 Requires Electrical Supply Yes Unit Depth (External) mm 600 UK 3 Pin Plug Yes	GTIN	5056105100515		
Pot Type Gastronorm Type of Heat Wet  Weights and Dimensions  Unit Height (External) mm 290 Requires Installation No Unit Width (External) mm 600 Requires Electrical Supply Yes Unit Depth (External) mm 600 UK 3 Pin Plug Yes	Key Specifications		Capacity	
Type of Heat Wet  Weights and Dimensions  Unit Height (External) mm 290 Requires Installation No Unit Width (External) mm 600 Requires Electrical Supply Yes Unit Depth (External) mm 600 UK 3 Pin Plug Yes	Drain Location	Front-mounted	Gastronorm Capacity	1 × GN1/2; 4 × GN1/4
Weights and Dimensions  Supply Connections  Unit Height (External) mm 290 Requires Installation No Unit Width (External) mm 600 Requires Electrical Supply Yes Unit Depth (External) mm 600 UK 3 Pin Plug Yes	Pot Type	Gastronorm		
Unit Height (External) mm 290 Requires Installation No Unit Width (External) mm 600 Requires Electrical Supply Yes Unit Depth (External) mm 600 UK 3 Pin Plug Yes	Type of Heat	Wet		
Unit Width (External) mm600Requires Electrical SupplyYesUnit Depth (External) mm600UK 3 Pin PlugYes	Weights and Dimensions		Supply Connections	
Unit Depth (External) mm 600 UK 3 Pin Plug Yes	Unit Height (External) mm	290	Requires Installation	No
	Unit Width (External) mm	600	Requires Electrical Supply	Yes
Net Weight Kg 18.9 Requires Hardwiring No	Unit Depth (External) mm	600	UK 3 Pin Plug	Yes
	Net Weight Kg	18.9	Requires Hardwiring	No

**Electrical Supply Rating Watts** 

Single Phase Amps

Single Phase Voltage

### Shipping

Packed Weight Kg	20.79
Packed Height cm	49.5
Packed Width cm	70
Packed Depth cm	70

### **Available Accessories**

CC6 Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal with Doors - W 600 mm

CN6 Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal without Doors - W 600 mm

Product Code: BM6AW Page Number: 1 Print Date: 11/10/2023







## **Available Accessories**


HC6
 Lincat Silverlink 600 Free-standing Heated Open-Top Pedestal with Doors - W 600 mm - 0.5 kW
 HCL6
 Lincat Silverlink 600 Free-standing Heated Pedestal with Legs and Doors - W 600 mm - 0.5 kW

**SLS6** Lincat Silverlink 600 Free-standing Floor Stand - for units W 600 mm

## **Technical Picture**













**Lincat Limited** 

Whisby Road,

Lincoln, LN6 3QZ,

United Kingdom

**Company No:** 2175448

A member company of

**Customer Care** 

**Tel:** +44 1522 875500

Email: care@lincat.co.uk

**Export Customers** 

**Tel:** +44 1522 875536

Email: export@lincat.co.uk

**Opening Hours** 

Monday - Friday:

8.30am - 5pm



Product Code: BM6AW Page Number: 3 Print Date: 11/10/2023