



F49/602/B - IMC Ventus VR60 Glass Froster [Front Load] - Glass Door - Black Painted Frame - H 800 mm - W 600 mm Designed to frost glasses and chill liqueurs, the VR60 can help commercial bars enhance the appearance of drinks and keep them colder for longer.

- Reduced 800mm height
- Wide range of options available to customise your glass froster, ensure a perfect fit in any bar
- Chills and frosts glasses, to enhance the taste and appearance of drinks
- Dynamic Air Distribution System coupled with efficient compressors and improved insulation ensures superior cooling times
- Rapid chill to -10°C to keep drinks colder for longer.

 Energy efficient EcoSmart controller - at the touch of a button, put the glass froster into its most economical state until next required

- Efficient design means up to 50 pint glasses can be chilled at the same time
- Front loading design ensures fast and easy access to ice cold glasses
- Stylish black painted exterior to suit any commercial bar setting
- UK 3 pin plug simply plug in and switch on

### **Specifications**

Summary		Power and Performance	
Brand	IMC	Total Power kW	0.667
Range	Ventus	Temperature Range °C	-10 constant
Power Type	Electric	IP Rating	IPX1
Jnit Type	Free-standing	Temperature Control	Electronic
vailable in UK Only	No		
JK Warranty	2 Years Parts and Labour Warranty		
Export Warranty	Contact your local dealer		
GTIN	5056105197157		
Key Specifications		Capacity	
Door Hinge	Right	Capacity Glasses	50 x standard pint
Door Location	Front	Capacity Litres	108
ockable Door	Yes		
Colour	Black Painted		
Number of Doors	1		
Number of Shelves included	2		
Number of Shelf Positions	29		
Refrigerant Type	R404a		
Type of Lighting	LED		
Weights and Dimensions		Supply Connections	
Jnit Height (External) mm	800	Requires Installation	No
Jnit Width (External) mm	600	Requires Electrical Supply	Yes
Jnit Depth (External) mm	500	UK 3 Pin Plug	Yes
leight (Internal) mm	655	Requires Hardwiring	No
Vidth (Internal) mm	526	Electrical Supply Rating Watts	667
Depth (Internal) mm	377	Single Phase Amps	2.90
Shelf Dimensions Width mm	510	Single Phase Voltage	240
Shelf Dimensions Depth mm	373		
let Weight Kg	57.5		

## **i**mc

# Ventus

### Shipping

Packed Weight Kg	63.25
Packed Height cm	106
Packed Width cm	67
Packed Depth cm	58

### **Available Options** Door Type VS493 VS493 - Change to Fixing Point Glass Door VS653 VS653 - Change to L/H Fixing Point Solid Door VS657 VS657 - Change to Fixing Point Solid Door VS683 VS683 - Change to L/H Fixing Point Glass Door VS795 VS795 - Change to Solid Door VS797 VS797 - Change to Left Hinged Solid Door VS838 VS838 - Change to Left Hinged Glass Door Wood Cladding VS404 VS404 - Wood Cladding Kit - Add to F-Point Door Handle Type VS446HOR VS446HOR - Short Horizontal Handle VS446VER VS446VER - Short Vertical Handle VS447HOR VS447HOR - Long Horizontal Handle VS447VER VS447VER - Long Vertical Handle Lighting VS852 VS852 - Change to Red LED Lights VS853 VS853 - Change to Green LED Lights VS854 VS854 - Change to Blue LED Lights Shelving Type VS359 VS359 - Change to Wine Shelving VS399 VS399 - Change to Perforated Shelving EU Plug VS401 VS401 - Change to EU Plug De-Gassed VS1017 VS1017 - De-Gassed for Air Freight **Available Accessories**

A12/091/Z1	Wire Shelf - Chrome - for M60 Bottle Cooler
A12/100	Wine Shelf - Chrome - for M60 Bottle Cooler
S76/048	Perforated Shelf - for V60 - 500D



# Lincat frifri

### Lincat Limited

Whisby Road, Lincoln, LN6 3QZ,

United Kingdom

Company No: 2175448

A member company of



## Customer Care

Tel: +44 1522 875500 Email: care@lincat.co.uk

### **Export Customers**

Tel: +44 1522 875536

Email: export@lincat.co.uk

### **Opening Hours**

Monday – Friday: 8.30am – 5pm