



F49/620 - IMC Ventus
VR60 Glass Froster [Front
Load] - Full Front Glass
Door - Stainless Steel
Frame - H 900 mm - W
600 mm

Designed to frost glasses and chill liqueurs, the VR60 can help commercial bars enhance the appearance of drinks and keep them colder for longer.

- ✓ Full front door for seamless integration
- ✓ Wide range of options available to customise your glass froster, ensure a perfect fit in any bar
- ✓ Chills and frosts glasses, to enhance the taste and appearance of drinks
- ✓ Dynamic Air Distribution System coupled with efficient compressors and improved insulation ensures superior cooling times
- ✓ Rapid chill to -10°C to keep drinks colder for longer
- ✓ Energy efficient EcoSmart controller - at the touch of a button, put the glass froster into its most economical state until next required
- ✓ Efficient design means up to 50 pint glasses can be chilled at the same time
- ✓ Front loading design ensures fast and easy access to ice cold glasses
- ✓ Stylish stainless steel exterior to suit any commercial bar setting
- ✓ UK 3 pin plug - simply plug in and switch on

Specifications

Summary

Brand	IMC
Range	Ventus
Power Type	Electric
Unit Type	Free-standing
Available in UK Only	No
UK Warranty	2 Years Parts and Labour Warranty
Export Warranty	Contact your local dealer
GTIN	5056105197089

Power and Performance

Total Power kW	0.667
Temperature Range °C	-10 constant
IP Rating	IPX1
Temperature Control	Electronic

Key Specifications

Door Hinge	Right
Door Location	Front
Lockable Door	No
Colour	Stainless Steel
Number of Doors	1
Door Type	Full front, glass
Number of Shelves included	2
Number of Shelf Positions	29
Refrigerant Type	R404a
Type of Lighting	LED

Capacity

Capacity Glasses	50 x standard pint
Capacity Litres	128

Weights and Dimensions	Supply Connections
------------------------	--------------------

Unit Height (External) mm	900	Requires Installation	No
Unit Width (External) mm	600	Requires Electrical Supply	Yes
Unit Depth (External) mm	500	UK 3 Pin Plug	Yes
Height (Internal) mm	755	Requires Hardwiring	No
Width (Internal) mm	526	Electrical Supply Rating Watts	667
Depth (Internal) mm	377	Single Phase Amps	2.90
Shelf Dimensions Width mm	510	Single Phase Voltage	240
Shelf Dimensions Depth mm	373		
Net Weight Kg	0		

Shipping

Packed Weight Kg	0
Packed Height cm	108
Packed Width cm	67
Packed Depth cm	59

Available Options

Door Type	
VS771	VS771 - Change to Right Hinged Cladded Door
VS777	VS777 - Change to Left Hinged Cladded Door
VS804	VS804 - Change to Solid Door
VS833	VS833 - Change to Left Hinged Solid Door
VS918	VS918 - Change to Left Hinged Glass Door
 Lighting	
VS852	VS852 - Change to Red LED Lights
VS853	VS853 - Change to Green LED Lights
VS854	VS854 - Change to Blue LED Lights
 Shelving Type	
VS359	VS359 - Change to Wine Shelving
VS399	VS399 - Change to Perforated Shelving
 EU Plug	
VS401	VS401 - Change to EU Plug
 De-Gassed	
VS1017	VS1017 - De-Gassed for Air Freight



Lincat Limited

Whisby Road,
Lincoln, LN6 3QZ,
United Kingdom

Company No: 2175448

A member company of



Customer Care

Tel: +44 1522 875500
Email: care@lincat.co.uk

Export Customers

Tel: +44 1522 875536
Email: export@lincat.co.uk

Opening Hours

Monday – Friday:
8.30am – 5pm