





F68/121 - IMC Vulture 825 In-tabling Food Waste Disposer - 3 Phase [4 wire] - W 360 mm - 2.2 kW Reliable, efficient, safe and easy to operate, the compact 825 Waste
Disposer allows operators to quickly and effectively remove waste, to create a safer and cleaner kitchen.

- Fast and efficient disposal of up to 600kg of food waste per hour.
- Handles up to 1350 covers per sitting ideal for large kitchens.
- For tough waste (red meat bones, cauliflower stalks and fish skins).
- Compact design, welded into tabling, for quick and easy loading.
- Manually reversible motor to extend operational life.
- Suitable for medium kitchens with three-phase, four-wire power supply.

Series 800 Series IP Rating  Power Type Electric Unit Type Welded into tabling  Available in UK Only No UK Warranty 2 Years Parts and Labour Warranty Export Warranty Contact your local dealer Mounting In-tabling GTIN 5056105199625  Key Specifications Capacity  Operator Safety Interlocks Type of Waste Covers Per Sitting Capacity Kg per Hou  Weights and Dimensions Supply Connect  Unit Height (External) mm 783 Requires Installation Unit Width (External) mm 360 Requires Electrical Supily Electrical Supily Rat Three Phase Amps Three Phase Voltage Water Supplied From	2.2 3 IP55
Range Vulture HP Series 800 Series IP Rating Power Type Electric Unit Type Welded into tabling Available in UK Only No UK Warranty 2 Years Parts and Labour Warranty Export Warranty Contact your local dealer In-tabling GTIN 5056105199625  Key Specifications Capacity  Operator Safety Interlocks Type of Waste Airbreak No Covers Per Sitting Capacity Kg per Hou Weights and Dimensions  Supply Connect Unit Height (External) mm 783 Requires Installation Unit Width (External) mm 360 Requires Electrical S Unit Depth (External) mm 530 UK 3 Pin Plug Net Weight Kg 51 Requires Hardwiring Electrical Supply Rat Three Phase Amps Three Phase Voltage Water Supplied From	3 IP55
Series 800 Series IP Rating  Power Type Electric Unit Type Welded into tabling Available in UK Only No UK Warranty 2 Years Parts and Labour Warranty Export Warranty Contact your local dealer Mounting In-tabling GTIN 5056105199625  Key Specifications Capacity  Operator Safety Interlocks Type of Waste Airbreak No Covers Per Sitting Capacity Kg per Hou  Weights and Dimensions  Supply Connect Unit Height (External) mm 783 Requires Installation Unit Width (External) mm 360 Requires Electrical S Unit Depth (External) mm 530 UK 3 Pin Plug Net Weight Kg 51 Requires Hardwiring Electrical Supply Rat Three Phase Amps Three Phase Voltage Water Supplied From	Tough waste
Power Type Unit Type Welded into tabling Available in UK Only No UK Warranty 2 Years Parts and Labour Warranty Export Warranty Contact your local dealer Mounting In-tabling GTIN 5056105199625  Key Specifications Capacity Operator Safety Airbreak No Covers Per Sitting Capacity Kg per Hou Weights and Dimensions Supply Connect Unit Height (External) mm 783 Requires Installation Unit Width (External) mm 530 Net Weight Kg Sit Requires Electrical Supply Rat Three Phase Amps Three Phase Amps Three Phase Voltage Water Supplied From	Tough waste
Unit Type Available in UK Only No UK Warranty Export Warranty  Export Warranty  Export Warranty  Contact your local dealer In-tabling GTIN  So56105199625  Key Specifications  Capacity  Operator Safety Airbreak  No Covers Per Sitting Capacity Kg per Hou  Weights and Dimensions  Supply Connect  Unit Height (External) mm 1830  Requires Installation Unit Width (External) mm 360  Requires Electrical Supply Rat Three Phase Amps Three Phase Amps Three Phase Voltage Water Supplied From	
Available in UK Only UK Warranty 2 Years Parts and Labour Warranty Export Warranty Contact your local dealer Mounting In-tabling GTIN 5056105199625  Key Specifications Capacity  Operator Safety Airbreak No Covers Per Sitting Capacity Kg per Hou  Weights and Dimensions Supply Connect  Unit Height (External) mm 783 Requires Installation Unit Width (External) mm 360 Requires Electrical Sunty  Net Weight Kg S1 Requires Hardwiring Electrical Supply Rat Three Phase Amps Three Phase Amps Three Phase Voltage Water Supplied From	
UK Warranty Export Warranty Contact your local dealer Mounting In-tabling GTIN 5056105199625  Key Specifications Capacity Operator Safety Airbreak No Covers Per Sitting Capacity Kg per Hou Weights and Dimensions Supply Connect Unit Height (External) mm Viit Height (External) mm Viit Height (External) mm Side Unit Depth (External) mm Side Unit Depth (External) mm Side Viit Height Kg Side Side Side Side Side Side Side Side	
Export Warranty  Mounting  GTIN  In-tabling  5058105199625  Key Specifications  Capacity  Operator Safety  Airbreak  No  Covers Per Sitting Capacity Kg per Hou  Weights and Dimensions  Supply Connect  Unit Height (External) mm  783  Requires Installation Unit Width (External) mm  360  Requires Electrical S  Unit Depth (External) mm  530  UK 3 Pin Plug  Net Weight Kg  Fequires Hardwiring Electrical Supply Rat Three Phase Amps Three Phase Voltage Water Supplied From	
Mounting In-tabling 5056105199625  Key Specifications Capacity  Operator Safety Interlocks Type of Waste Covers Per Sitting Capacity Kg per Hou Weights and Dimensions Supply Connect Unit Height (External) mm 783 Requires Installation Unit Width (External) mm 360 Requires Electrical Supply Context Unit Depth (External) mm 530 UK 3 Pin Plug Net Weight Kg 51 Requires Hardwiring Electrical Supply Rat Three Phase Amps Three Phase Voltage Water Supplied From	
GTIN 5056105199625  Key Specifications Capacity  Operator Safety Interlocks Type of Waste Covers Per Sitting Capacity Kg per Hou Weights and Dimensions Supply Connect  Unit Height (External) mm 783 Requires Installation Unit Width (External) mm 360 Requires Electrical Supply Connect  Unit Depth (External) mm 530 UK 3 Pin Plug  Net Weight Kg 51 Requires Hardwiring Electrical Supply Rat Three Phase Amps Three Phase Voltage Water Supplied From	
Key Specifications  Capacity  Operator Safety Airbreak  No  Covers Per Sitting Capacity Kg per Hou  Weights and Dimensions  Supply Connect  Unit Height (External) mm  783  Requires Installation Unit Width (External) mm  360  Requires Electrical Supply  UK 3 Pin Plug  Net Weight Kg  51  Requires Hardwiring Electrical Supply Rat Three Phase Amps Three Phase Voltage Water Supplied From	
Operator Safety Airbreak  No Covers Per Sitting Capacity Kg per Hou  Weights and Dimensions  Supply Connect  Unit Height (External) mm 783 Requires Installation Unit Width (External) mm 360 Requires Electrical S  Unit Depth (External) mm 530 UK 3 Pin Plug  Net Weight Kg 51 Requires Hardwiring Electrical Supply Rat Three Phase Amps Three Phase Voltage Water Supplied From	
Airbreak  No  Covers Per Sitting Capacity Kg per Hou  Weights and Dimensions  Supply Connect  Unit Height (External) mm  783  Requires Installation Requires Electrical S  Unit Depth (External) mm  530  UK 3 Pin Plug  Net Weight Kg  51  Requires Hardwiring Electrical Supply Rat  Three Phase Amps  Three Phase Voltage Water Supplied From	
Airbreak  No  Covers Per Sitting Capacity Kg per Hou  Weights and Dimensions  Supply Connect  Unit Height (External) mm  783  Requires Installation Requires Electrical S  Unit Depth (External) mm  530  UK 3 Pin Plug  Net Weight Kg  51  Requires Hardwiring Electrical Supply Rat  Three Phase Amps Three Phase Voltage Water Supplied From	
Weights and Dimensions  Supply Connect  Unit Height (External) mm 783 Requires Installation Unit Width (External) mm 360 Requires Electrical S Unit Depth (External) mm 530 UK 3 Pin Plug Net Weight Kg 51 Requires Hardwiring Electrical Supply Rat Three Phase Amps Three Phase Voltage Water Supplied From	1350
Weights and Dimensions  Supply Connect  Weight (External) mm  783  Requires Installation Requires Electrical S  Unit Depth (External) mm  530  UK 3 Pin Plug  Net Weight Kg  51  Requires Hardwiring Electrical Supply Rat Three Phase Amps Three Phase Voltage Water Supplied From	600
Unit Height (External) mm  783  Requires Installation Requires Electrical S Unit Depth (External) mm  530  UK 3 Pin Plug Net Weight Kg  51  Requires Hardwiring Electrical Supply Rat Three Phase Amps Three Phase Voltage Water Supplied From	
Unit Width (External) mm  360  Requires Electrical S  UK 3 Pin Plug  Net Weight Kg  51  Requires Hardwiring  Electrical Supply Rat  Three Phase Amps  Three Phase Voltage  Water Supplied From	ons
Unit Depth (External) mm 530 UK 3 Pin Plug Net Weight Kg 51 Requires Hardwiring Electrical Supply Rat Three Phase Amps Three Phase Voltage Water Supplied From	Yes
Net Weight Kg 51 Requires Hardwiring Electrical Supply Rat Three Phase Amps Three Phase Voltage Water Supplied From	<b>pply</b> Yes
Electrical Supply Rat Three Phase Amps Three Phase Voltage Water Supplied From	No
Three Phase Amps Three Phase Voltage Water Supplied From	Yes
Three Phase Voltage Water Supplied From	ng Watts 2200
Water Supplied From	5.3
	400
	Storage cistern
Water Connection Pr	ssure Bar 0.4
Drain Connection	2" BSP threaded flange, connected to 54mm piping;
Water Connection	15mm
Shipping	
Packed Weight Kg 56.1	
Packed Height cm 104	
Packed Width cm 63	





## **Available Options**


MAG CUTLERY SAVER


**VS167** 700/800/904/904X MAGNETIC CUTLERY SAVER


WATER FLOW CONTROL

**VS357** 825 WATER FLOW CONTROL

## **Technical Picture**













**Lincat Limited** 

Whisby Road,

Lincoln, LN6 3QZ,

United Kingdom

Offica Kingdom

**Company No:** 2175448

A member company of

**Customer Care** 

**Tel:** +44 1522 875500

Email: care@lincat.co.uk

**Export Customers** 

**Tel:** +44 1522 875536

Email: export@lincat.co.uk

**Opening Hours** 

Monday - Friday:

8.30am - 5pm