



ICC102G/N - RATIONAL iCombi Classic - Model 10-2/1 - Natural Gas Freestanding Combi Oven - 40 kW The RATIONAL iCombi Classic 10-2/1 is truly multitalented, and will quickly become the indispensable assistant in your kitchen.

- 10 x GN 2/1 capacity, ideal for restaurants and food service applications
- Produce consistent high quality results with crisp crusts, attractive diamond grill patterns, or crispy breaded products
- Easy to use controls, with recognisable symbols and dial with a push function
- Digital display of cooking chamber humidity, time, and adjustable temperature

- Store up to 100 cooking programmes with as many as 12 steps
- Steam mode with steam regulation in 10% stages, together with consistent cooking cabinet temperature and optimal steam saturation, provides a uniform cooking process
- Advantages of steam combined with benefits of convection heat: short cooking time, reduction in shrinkage and intensive aromas with appetising colours. No cooking loss, no drying, high quality
- 4 automatic cleaning programmes, and integrated hand shower

Summary		Power and Performance	
Brand	Lincat	Total Power kW	40
Range	RATIONAL	Temperature Range °C	30-300
Series	iCombi Classic	IP Rating	IPX5
Power Type	Gas	Temperature Control	Electronic
as Type	Natural Gas	Oven Rating kW	Steam connection = 40.0; Hot air
nit Type	Free-standing	Oven Rating KW	connection = 40.0
vailable in UK Only	Yes		
UK Warranty	RATIONAL 2 Years Parts and Labour		
<b>,</b>	Warranty		
Key Specifications		Capacity	
ype of Lighting	LED	Gastronorm Capacity	10 x GN2/1
lumber of Grids included	0	Portions per Day	150-300
Weights and Dimensions		Supply Connections	
Init Height (External) mm	1064	Requires Installation	Yes
Init Width (External) mm	1072	Requires Electrical Supply	Yes
Init Depth (External) mm	1042	UK 3 Pin Plug	Yes
let Weight Kg	184	Requires Hardwiring	No
		<b>Electrical Supply Rating Watts</b>	1,500
		Single Phase Amps	13
		Single Phase Voltage	230
		Gas Connection BSP	3/4"
		Gas Pressure Natural mbar	18-25
		Total heat input at full rate Natural kW	40
		Water Connection Pressure Bar	6
		Drain Connection	DN 50 mm
		Water Connection	3/4"





## **Shipping**

 Packed Weight Kg
 202.4

 Packed Height cm
 125

 Packed Width cm
 117.5

 Packed Depth cm
 115.5

## **Available Accessories**

60.70.464

RATIONAL Applicance Connection Kit - Model 6-1/1-20-2/1 - with Adapter for Model XS  $\,$ 



**Lincat Limited** 

Whisby Road,

Lincoln, LN6 3QZ,

United Kingdom

Officea Mingaoini

**Company No:** 2175448

A member company of

**Customer Care** 

**Tel:** +44 1522 875500

Email: care@lincat.co.uk

**Export Customers** 

**Tel:** +44 1522 875536

Email: export@lincat.co.uk

**Opening Hours** 

Monday - Friday:

8.30am - 5pm