



ICC102G/P - RATIONAL iCombi Classic - Model 10-2/1 - Propane Gas Freestanding Combi Oven - 40 kW

- 10 x GN 2/1 capacity, ideal for restaurants and food service applications
- Produce consistent high quality results with crisp crusts, attractive diamond grill patterns, or crispy breaded products
- Easy to use controls, with recognisable symbols and dial with a push function
- Digital display of cooking chamber humidity, time, and adjustable temperature

The RATIONAL iCombi Classic 10-2/1 is truly multitalented, and will quickly become the indispensable assistant in your kitchen.

- Store up to 100 cooking programmes with as many as 12 steps
- Steam mode with steam regulation in 10% stages, together with consistent cooking cabinet temperature and optimal steam saturation, provides a uniform cooking process
- Advantages of steam combined with benefits of convection heat: short cooking time, reduction in shrinkage and intensive aromas with appetising colours. No cooking loss, no drying, high quality
- 4 automatic cleaning programmes, and integrated hand shower

Specifications

Summary		Power and Performance	
Brand	Lincat	Total Power kW	40
Range	RATIONAL	Temperature Range °C	30-300
Series	iCombi Classic	IP Rating	IPX5
Power Type	Gas	Temperature Control	Electronic
Gas Type	Propane Gas	Oven Rating kW	Steam connection = 40.0;Hot air
Unit Type	Free-standing		connection = 40.0
Available in UK Only	Yes		
UK Warranty	RATIONAL 2 Years Parts and Labour Warranty		
Key Specifications		Capacity	
Type of Lighting	LED	Gastronorm Capacity	10 × GN2/1
Number of Grids included	0	Portions per Day	150-300
Weights and Dimensions		Supply Connections	
Unit Height (External) mm	1064	Requires Installation	Yes
Unit Width (External) mm	1072	Requires Electrical Supply	Yes
Unit Depth (External) mm	1042	UK 3 Pin Plug	Yes
Net Weight Kg	184	Requires Hardwiring	No
		Electrical Supply Rating Watts	1,500
		Single Phase Amps	13
		Single Phase Voltage	230
		Gas Connection BSP	3/4"
		Gas Pressure Propane mbar	25-57.5
		Total heat input at full rate Propane kW	40
		Water Connection Pressure Bar	6
		Drain Connection	DN 50 mm
		Water Original ten	
		Water Connection	3/4"





ShippingPacked Weight Kg202.4Packed Height cm125Packed Width cm117.5Packed Depth cm115.5

Available Accessories

60.70.464

RATIONAL Applicance Connection Kit - Model 6-1/1-20-2/1 - with Adapter for Model XS

Lincat fift

Lincat Limited

Whisby Road, Lincoln, LN6 30Z,

United Kingdom

Company No: 2175448

A member company of



Customer Care

Tel: +44 1522 875500

Email: care@lincat.co.uk

Export Customers

Tel: +44 1522 875536

Email: export@lincat.co.uk

Opening Hours

Monday – Friday: 8.30am – 5pm