



## ICP061ESP - RATIONAL iCombi Pro - Model 6-1/1 -Electric Free-standing Combi Oven - 10.8 kW

The intelligent RATIONAL iCombi Pro 6-1/1 thinks, learns, watches and adapts, dynamically responding to requirements.

- 6 x GN 1/1 capacity, ideal for restaurants and foodservice applications
- Four intelligent assistants for climate management, cooking operation, production management, and cleaning
- iDensityControl delivers consistent and uniform results. At the same time, the intuitive operating concept provides the highest level of user support and less chance of errors
- iCookingSuite continuously checks the condition of the food against the desired result, calculates the cooking progress and intelligently adjusts the temperature to achieve. It also allows you to change the desired result, browning or cooking parameters during the cooking process

- iProductionManager optimises food production, simply place the dish on the display and it will show you what else you can produce at the same time
- iCareSystem 9 cleaning programmes, including the ultrafast interim clean in approx. 12 minutes
- WiFi interface for connected cooking and easy access to HACCP documentation
- Single phase installation

Specifications			
Summary		Power and Performance	
Brand	Lincat	Total Power kW	10.8
Range	RATIONAL	Temperature Range °C	30-300
Series	iCombi Pro	IP Rating	IPX5
Power Type	Electric	Temperature Control	Electronic
Unit Type	Free-standing	Oven Rating kW	Steam connection = 9.0; Hot air
Available in UK Only	Yes	Grown warming war	connection = 10.3
UK Warranty	RATIONAL 2 Years Parts and Labour Warranty		
Key Specifications		Capacity	
Type of Lighting	LED	Gastronorm Capacity	6 x GN1/1
Number of Grids included	0	Portions per Day	30-100
Weights and Dimensions		Supply Connections	
Unit Height (External) mm	804	Requires Installation	Yes
Unit Width (External) mm	850	Requires Electrical Supply	Yes
Unit Depth (External) mm	842	UK 3 Pin Plug	No
Net Weight Kg	99	Requires Hardwiring	Yes
		<b>Electrical Supply Rating Watts</b>	10,800
		Single Phase Amps	50
		Single Phase Voltage	230
		Water Connection Pressure Bar	6
		Drain Connection	DN 50 mm
		Water Connection	3/4"





## **Shipping**

Packed Weight Kg 108.9 Packed Height cm 96 Packed Width cm 93.5 Packed Depth cm 95.5

## **Available Accessories**

60.70.464

RATIONAL Applicance Connection Kit - Model 6-1/1-20-2/1 - with Adapter for Model XS  $\,$ 



**Lincat Limited** 

Whisby Road,

Lincoln, LN6 3QZ,

United Kingdom

**Company No:** 2175448

**Customer Care** 

**Tel:** +44 1522 875500

Email: care@lincat.co.uk

**Export Customers** 

**Tel:** +44 1522 875536

Email: export@lincat.co.uk

**Opening Hours** 

Monday - Friday:

8.30am - 5pm

A member company of



**Print Date:** 28/10/2022 Product Code: ICP061ESP Page Number: 2