



ICP102G/N - RATIONAL iCombi Pro - Model 10-2/1 - Natural Gas Freestanding Combi Oven - 40 kW The intelligent RATIONAL iCombi Pro 10-2/1 thinks, learns, watches and adapts, dynamically responding to requirements.

- 10 x GN 2/1 capacity, ideal for restaurants and foodservice applications
- Four intelligent assistants for climate management, cooking operation, production management, and cleaning
- iDensityControl delivers consistent and uniform results. At the same time, the intuitive operating concept provides the highest level of user support and less chance of errors
- iCookingSuite continuously checks the condition of the food against the desired result, calculates the cooking progress and intelligently adjusts the temperature to achieve. It also allows you to change the desired result, browning or cooking parameters during the cooking process

- iProductionManager optimises food production, simply place the dish on the display and it will show you what else you can produce at the same time
- iCareSystem 9 cleaning programmes, including the ultrafast interim clean in approx. 12 minutes
- WiFi interface for connected cooking and easy access to HACCP documentation

Specifications			
Summary		Power and Performance	
Brand	Lincat	Total Power kW	40
Range	RATIONAL	Temperature Range °C	30-300
Series	iCombi Pro	IP Rating	IPX5
Power Type	Gas	Temperature Control	Electronic
Gas Type	Natural Gas	Oven Rating kW	Steam connection = 40.0; Hot air
Unit Type	Free-standing		connection = 40.0
Available in UK Only	Yes		
UK Warranty	RATIONAL 2 Years Parts and Labour Warranty		

Key Specifications		Capacity	
Type of Lighting	LED	Gastronorm Capacity	10 x GN2/1
Number of Grids included	0	Portions per Day	150-300





Weights and Dimensions		Supply Connections	Supply Connections	
Unit Height (External) mm	1064	Requires Installation	Yes	
Unit Width (External) mm	1072	Requires Electrical Supply	Yes	
Unit Depth (External) mm	1042	UK 3 Pin Plug	Yes	
Net Weight Kg	192	Requires Hardwiring	No	
		<b>Electrical Supply Rating Watts</b>	1,500	
		Single Phase Amps	13	
		Single Phase Voltage	230	
		Gas Connection BSP	3/4"	
		Gas Pressure Natural mbar	18-25	
		Total heat input at full rate Natural kW	40	
		Water Connection Pressure Bar	6	
		Drain Connection	DN 50 mm	
		Water Connection	3/4"	
01.1				

## Shipping

 Packed Weight Kg
 211.2

 Packed Height cm
 125

 Packed Width cm
 117.5

 Packed Depth cm
 115.5

## **Available Accessories**

60.70.464

RATIONAL Applicance Connection Kit - Model 6-1/1-20-2/1 - with Adapter for Model XS  $\,$ 



Lincat Limited Customer Care

Whisby Road, **Tel:** +44 1522 875500

Lincoln, LN6 3QZ, **Email:** care@lincat.co.uk

United Kingdom

**Company No:** 2175448

A member company of

**Export Customers** 

**Tel:** +44 1522 875536

Email: export@lincat.co.uk

**Opening Hours** 

Monday – Friday:

8.30am - 5pm