



ICPXSSP - RATIONAL iCombi Pro - Model XS 6-2/3 - Electric Counter-top Combi Oven - 5.3 kW

- The perfect solution where space is at a premium, a compact 6 x GN 2/3 unit with exactly the same performance, intelligence and efficiency as larger models
- Four intelligent assistants for climate management, cooking operation, production management, and cleaning
- iDensityControl delivers consistent and uniform results. At the same time, the intuitive operating concept provides the highest level of user support and less chance of errors
- iCookingSuite continuously checks the condition of the food against the desired result, calculates the cooking progress and intelligently adjusts the temperature to achieve. It also allows you to change the desired result, browning or cooking parameters during the cooking process

The intelligent RATIONAL iCombi Pro XS 6-2/3 thinks, learns, watches and adapts, dynamically responding to requirements.

- iProductionManager optimises food production, simply place the dish on the display and it will show you what else you can produce at the same time
- iCareSystem 9 cleaning programmes, including the ultrafast interim clean in approx. 12 minutes
- WiFi interface for connected cooking and easy access to HACCP documentation
- Single phase installation

0			
- 5	pecif	icat	ions
-		out	

Summary		Power and Performance	
Brand	Lincat	Total Power kW	5.3
Range	RATIONAL	Temperature Range °C	30-300
Series	iCombi Pro	IP Rating	IPX5
Power Type	Electric	Temperature Control	Electronic
Unit Type	Counter-top	Oven Rating kW	Steam connection = 5.0;Hot air
Available in UK Only	Yes		connection = 5.0
UK Warranty	RATIONAL 2 Years Parts and Labour Warranty		
Key Specifications		Capacity	
Type of Lighting	LED	Gastronorm Capacity	6 x GN2/3
Number of Grids included	0	Portions per Day	20-80
Weights and Dimensions		Supply Connections	
Unit Height (External) mm	594	Requires Installation	Yes
Unit Width (External) mm	655	Requires Electrical Supply	Yes
Unit Depth (External) mm	621	UK 3 Pin Plug	Νο
Net Weight Kg	74	Requires Hardwiring	Yes
		Electrical Supply Rating Watts	5,300
		Single Phase Amps	25
		Single Phase Voltage	230
		Water Connection Pressure Bar	6
		Drain Connection	DN 40 mm
		Water Connection	3/4"





## ShippingPacked Weight Kg81.4Packed Height cm95Packed Width cm90Packed Depth cm77

## **Available Accessories**

60.70.464

RATIONAL Applicance Connection Kit - Model 6-1/1-20-2/1 - with Adapter for Model XS

## Lincat fift

## Lincat Limited

Whisby Road, Lincoln, LN6 30Z,

United Kingdom

Company No: 2175448

A member company of



**Customer Care** 

Tel: +44 1522 875500

Email: care@lincat.co.uk

Export Customers

Tel: +44 1522 875536

Email: export@lincat.co.uk

**Opening Hours** 

Monday – Friday: 8.30am – 5pm