



PD211M31G0 - FriFri Precision 211 Electric Drop-in Single Tank Fryer - 1 Basket - W 200 mm - 9.0 kW For the chef who wants superb temperature control for consistently excellent results, a drop in Precision 211 is the fryer of choice.

- Electronic temperature control and powerful elements maintains oil to within +/-1°C of the temperature selected, reducing oil usage and ensuing your food always has that all-important crunch.
- With one cooking programme, perfect for when you want to cook the same product time after time, to the same exacting standards.
- Digital timer displays the count down, with a buzzer sounding at the end of the cook cycle.
- Temperature view shows current oil temperature, enabling you to make an informed decision as to when to start cooking.

- Are there more fries than last time? Adaptive cooking automatically adjusts the cooking times to suit your batch size ensuring you never serve undercooked food.
- Keeping your oil in peak condition! Optional xFri® filters the oil at the push of a button and returns oil to the tank. Filter the oil safely, even while it's still hot, mid service if necessary, and resume frying in minutes – so easy there is no excuse not to!
- Raising food to the next level. Perfect for kitchens where you don't have time for constant supervision, optional LiftFri® automatic basket lifting system lifts food at the end of the cycle to prevent overcooking.
- Pressed tank for strength and durability.
 Radiused corners for easy cleaning. Hinged elements with two tilt positions for draining and cleaning.

Summary		Power and Performance	
Brand	FriFri	Total Power kW	9.0
Range	Precision	Temperature Range °C	60-190
ower Type	Electric	IP Rating	IPX4
Init Type	Drop in	Temperature Control	Electronic
vailable in UK Only	No		
K Warranty	2 Years Parts and Labour Warranty		
xport Warranty	Contact your local dealer		
TIN	5056105122036		
(ey Specifications		Capacity	
Number of Baskets	1	Product Output per Hour	20kg fries - 7mm[frozen]
umber of Tanks	1	Capacity Litres	7.5-9.0
ravity Filtration	Yes		
umped Filtration	No		
rain Location	Through the body		





Weights and Dimensions		Supply Connections	
Unit Height (External) mm	809	Requires Installation	Yes
Unit Width (External) mm	197.5	Requires Electrical Supply	Yes
Unit Depth (External) mm	630	UK 3 Pin Plug	No
Net Weight Kg	40	Requires Hardwiring	Yes
		Electrical Supply Rating Watts	9,000
		Single Phase Amps	39.1
		Single Phase Voltage	230
		Three Phase Amps	L1=13.0; L2=13.0; L3=13.0
		Three Phase Voltage	400
		Number of Supply Cables	1
Shipping			

 Packed Weight Kg
 35.0933

 Packed Height cm
 72

 Packed Width cm
 49

 Packed Depth cm
 80

Available Options

Oil Pump

OP1 10il Pump

Basket Lift

OL1 1 Basket Lift



Lincat Limited

Whisby Road,

Lincoln, LN6 3QZ,

United Kingdom

Company No: 2175448

A member company of

Customer Care

Tel: +44 1522 875500

Email: care@lincat.co.uk

Export Customers

Tel: +44 1522 875536

Email: export@lincat.co.uk

Opening Hours

Monday - Friday:

8.30am - 5pm