



PD412L31G0 - FriFri Precision 412 Electric Drop-in Single Tank Fryer - 2 Baskets - W 400 mm - 15.0 kW For the chef who wants superb temperature control for consistently excellent results, a drop in Precision 412 is the fryer of choice.

- ◆ Electronic temperature control and powerful elements maintains oil to within +/-1°C of the temperature selected, reducing oil usage and ensuing your food always has that all-important crunch.
- With one cooking programme, perfect for when you want to cook the same product time after time, to the same exacting standards.
- Digital timer displays the count down, with a buzzer sounding at the end of the cook cycle.
- Temperature view shows current oil temperature, enabling you to make an informed decision as to when to start cooking.

- Are there more fries than last time? Adaptive cooking automatically adjusts the cooking times to suit your batch size ensuring you never serve undercooked food.
- Keeping your oil in peak condition! Optional xFri@ filters the oil at the push of a button and returns oil to the tank. Filter the oil safely, even while it's still hot, mid service if necessary, and resume frying in minutes – so easy there is no excuse not to!
- Raising food to the next level. Perfect for kitchens where you don't have time for constant supervision, optional LiftFri® automatic basket lifting system lifts food at the end of the cycle to prevent overcooking.
- Pressed tank for strength and durability. Radiused corners for easy cleaning. Hinged elements with two tilt positions for draining and cleaning.

## **Specifications Summary Power and Performance** Brand Total Power kW FriFri 15.0 Range Precision Temperature Range °C 60-190 Power Type IP Rating IPX4 Electric **Temperature Control** Unit Type Drop in Electronic Available in UK Only No **UK Warranty** 2 Years Parts and Labour Warranty **Export Warranty** Contact your local dealer **GTIN** 5056105122074 **Key Specifications** Capacity Number of Baskets **Product Output per Hour** 2 36kg fries - 7mm [frozen] **Number of Tanks Capacity Litres** 17.0-20.5 **Gravity Filtration** Yes **Pumped Filtration** No **Drain Location** Through the body





Weights and Dimensions		Supply Connections	Supply Connections	
Unit Height (External) mm	809	Requires Installation	Yes	
Unit Width (External) mm	397.5	Requires Electrical Supply	Yes	
Unit Depth (External) mm	630	UK 3 Pin Plug	No	
Net Weight Kg	62	Requires Hardwiring	Yes	
		<b>Electrical Supply Rating Watts</b>	15,000	
		Three Phase Amps	L1=21.7; L2=21.7; L3=21.7	
		Three Phase Voltage	400	
		Number of Supply Cables	1	
Shinning				

Shipping

Packed Weight Kg62.7Packed Height cm72Packed Width cm89Packed Depth cm80

## **Available Options**

Oil Pump

**OP1** 10il Pump

**Basket Lift** 

**OL1** 1 Basket Lift

**Baskets** 

**411\_1\_BASKET** 1 Basket **411\_2\_BASKETS** 2 Baskets

## **Available Accessories**

FZ411048

LARGE BASKET FOR 411 - 5MM MESH - COMPLETE WITH HANDLE



Lincat Limited Customer Care

Whisby Road, **Tel:** +44 1522 875500

Lincoln, LN6 3QZ, **Email:** care@lincat.co.uk

United Kingdom

**Company No:** 2175448

A member company of

**Export Customers** 

**Tel:** +44 1522 875536

Email: export@lincat.co.uk

**Opening Hours** 

Monday - Friday:

8.30am - 5pm