



Number of Tanks

**Gravity Filtration** 

Pumped Filtration Drain Location 2

Yes

Through the body

SD422L32G0 - FriFri Super Easy 422 Electric Drop-in Twin Tank Fryer with Filtration - 2 Baskets - W 400 mm - 2 x 7.5 kW When budget is a primary consideration, FriFri's unrivalled credentials, know-how and quality are still well within your reach. A drop in Super Easy 422 offers outstanding value with no compromise in quality or performance.

- Outstanding quality with no compromise in quality or performance.
- Mechanical thermostat maintains oil to within +/-8 °C of the temperature selected.
- Low watts density element with a large surface area in contact with the oil for fast recovery time and to prevent scorching which degrades oil.
- Keeping your oil in peak condition! Integral gravity filtration extends oil life by up to 75% saving you money on oil purchase and disposal costs. Optional xFri© filters the oil at the push of a button and returns oil to the tank. Filter the oil safely, even while it's still hot, mid service if necessary, and resume frying in minutes so easy there is no excuse not to!
- Pressed tank for strength and durability. Radiused corners for easy cleaning. Hinged elements with two tilt positions for draining and cleaning.
- Optimum Allergy Control. Supplied with separate oil buckets, and can be supplied with separate pumped filtration systems, providing completely segregated gravity filtration for optimum allergen control or to cater for dietary preferences.

2 x 7.5-9.0

## **Specifications Summary Power and Performance Brand** FriFri Total Power kW $2 \times 7.5$ Range Super Easy Temperature Range °C 95-190 **Power Type IP Rating** IPX4 Electric **Unit Type Temperature Control** Drop in Mechanical Available in UK Only Nο **UK Warranty** 2 Years Parts and Labour Warranty **Export Warranty** Contact your local dealer GTIN 5056105123620 **Key Specifications** Capacity **Number of Baskets Product Output per Hour** 2 2 x 17kg fries - 7mm [frozen]

Capacity Litres





| Weights and Dimensions    |       | Supply Connections             | Supply Connections                    |  |
|---------------------------|-------|--------------------------------|---------------------------------------|--|
| Unit Height (External) mm | 849   | Requires Installation          | Yes                                   |  |
| Unit Width (External) mm  | 397.5 | Requires Electrical Supply     | Yes                                   |  |
| Unit Depth (External) mm  | 630   | UK 3 Pin Plug                  | No                                    |  |
| Net Weight Kg             | 32    | Requires Hardwiring            | Yes                                   |  |
|                           |       | Electrical Supply Rating Watts | 2 × 7,500                             |  |
|                           |       | Three Phase Amps               | L1=2 x 10.9; L2=2 x 10.9; L3=2 x 10.9 |  |
|                           |       | Three Phase Voltage            | 400                                   |  |
|                           |       | Number of Supply Cables        | 2                                     |  |
|                           |       |                                |                                       |  |

Shipping

 Packed Weight Kg
 35.2

 Packed Height cm
 72

 Packed Width cm
 89

 Packed Depth cm
 80

## **Available Options**

Oil Pump

**OP1** 1 0il Pump

 **OP2** 2 0il Pumps



**Lincat Limited** 

Whisby Road,

Lincoln, LN6 3QZ, United Kingdom

**Company No:** 2175448

A member company of

**Customer Care** 

**Tel:** +44 1522 875500

Email: care@lincat.co.uk

**Export Customers** 

**Tel:** +44 1522 875536

Email: export@lincat.co.uk

**Opening Hours** 

Monday - Friday:

8.30am - 5pm