



TL422L12G0 - FriFri Touch 422 Electric Free-standing Twin Tank Fryer - 2 Baskets - W 400 mm - 2 x 7.5 kW - Single Phase

For those who run the busiest professional kitchens and refuse to compromise on quality, a Touch 422 is your newest kitchen assistant, helping you to deliver quality results every time.

- ✓ 24 one touch icon driven menu items, meaning regardless of the operator, at one touch deliver precisely the same results every time.
- ✓ Are there more fries than last time? Adaptive cooking automatically adjusts the cooking times to suit your batch size ensuring you never serve undercooked food.
- ✓ The 4.3" OPad is intuitive, easy to use and provides the wider functionality that only a touch screen can deliver.
- ✓ Easy-View Traffic Light Status – ColourCue. Great for busy and noisy kitchens, ColourCue shows you the status of your fryer at a glance: red - attention required such as unload; amber - pre-heating; green - ready to fry.
- ✓ Understand your energy usage. Customise the eco settings by temperature to suit your operation. View where you can make savings with detailed analysis of the fryer's energy usage over the last 8 hours, 24 hours, 7 days and 28 days.
- ✓ Keeping your oil in peak condition! FriFri Oil Assistant and optional xFri© to easily monitor the condition of oil with the onscreen oil status. When prompted filter the oil even while its still hot, mid service if necessary, and resume frying in under five minutes. It is so quick and easy there is no excuse not to!
- ✓ Raising food to the next level. Perfect for kitchens where you don't have time for constant supervision, optional LiftFri© automatic basket lifting system lifts food at the end of the cycle to prevent overcooking.
- ✓ Optimum Allergy Control. Supplied with separate oil buckets, and can be supplied with separate pumped filtration systems, providing completely segregated gravity filtration for optimum allergen control or to cater for dietary preferences.
- ✓ Pressed tank for strength and durability. Radiused corners for easy cleaning. Hinged elements with two tilt positions for draining and cleaning.
- ✓ Data driven quality. For the ultimate repeatable results view your fryer usage data hours of operation coupled with the number of cook and filter cycles. For multi-site operations configure and clone your menu easily via USB.
- ✓ Consistency across sites. Ensure consistent, great quality results across multiple sites, easily via USB.
- ✓ Invest in the future of your business with a Touch fryer. With superior construction, an industry leading high output from minimal footprint, and with easy to apply USB software updates, Touch will ensure happy, satisfied customers for many years to come.
- ✓ Single phase.

Specifications

Summary

| | |
|-----------------------------|-----------------------------------|
| Brand | FriFri |
| Range | Touch |
| Power Type | Electric |
| Unit Type | Free-standing |
| Available in UK Only | No |
| UK Warranty | 2 Years Parts and Labour Warranty |
| Export Warranty | Contact your local dealer |
| GTIN | 5056105123194 |

Power and Performance

| | |
|-----------------------------|------------|
| Total Power kW | 2 x 7.5 |
| Temperature Range °C | 40-190 |
| IP Rating | IPX4 |
| Temperature Control | Electronic |

| Key Specifications | | Capacity | |
|--------------------|------------------|-------------------------|-------------------------------|
| Number of Baskets | 2 | Product Output per Hour | 2 x 18kg fries - 7mm [frozen] |
| Number of Tanks | 2 | Capacity Litres | 2 x 7.5-9.0 |
| Gravity Filtration | Yes | | |
| Pumped Filtration | No | | |
| Drain Location | Through the body | | |

| Weights and Dimensions | | Supply Connections | |
|---------------------------|-------|--------------------------------|-----------|
| Unit Height (External) mm | 994 | Requires Installation | Yes |
| Unit Width (External) mm | 397.5 | Requires Electrical Supply | Yes |
| Unit Depth (External) mm | 650 | UK 3 Pin Plug | No |
| Net Weight Kg | 79 | Requires Hardwiring | Yes |
| | | Electrical Supply Rating Watts | 2 x 7,500 |
| | | Single Phase Amps | 2 x 32.6 |
| | | Single Phase Voltage | 230 |
| | | Number of Supply Cables | 2 |

| Shipping | |
|------------------|-------|
| Packed Weight Kg | 81.84 |
| Packed Height cm | 113 |
| Packed Width cm | 79 |
| Packed Depth cm | 52 |

| Available Options | |
|---------------------|---|
| Oil Pump | |
| OP1 | 1 Oil Pump |
| OP2 | 2 Oil Pumps |
| Basket Lift | |
| OL1 | 1 Basket Lift |
| OL2 | 2 Basket Lifts |
| Legs/Castors | |
| OC200 | OC200 - 2 Castors [Fixed at Rear] + 2 Legs [at Front] |
| OC400 | OC400 - 4 Castors [2 Fixed at Rear + 2 Swivel at Front] |



Lincat Limited

Whisby Road,
Lincoln, LN6 3QZ,
United Kingdom

Company No: 2175448

A member company of



Customer Care

Tel: +44 1522 875500
Email: care@lincat.co.uk

Export Customers

Tel: +44 1522 875536
Email: export@lincat.co.uk

Opening Hours

Monday – Friday:
8.30am – 5pm