



Technical data sheet for

EHT10-L HUMIDIFIED HOLDING CABINET

10 Tray Electric Humidified Holding Cabinet TOUCH CONTROL





FHT10 I

Unit shall be a Blue Seal electrically heated Turbofan Humidified Holding Cabinet. The holding cabinet shall have double skin construction with stainless steel interior and exterior sides, front and top. Door shall be side hinged. Unit shall have capacity for 10 half size sheet pans or 10 1/1GN or 12" x 20" steam pans. A single speed fan shall gently and evenly circulate air around the cabinet. Cabinet shall be controlled by a 5.7" Touch Screen control with individual shelf timers and cabinet temperature control and humitity level control. Holding cabinet shall be mounted on castors, with two rigid castors at rear and two castors, swivel and wheel lock at front. Holding Cabinet shall operate independently or in conjunction with Blue Seal Turbofan E33T Convection Oven. Holding Cabinet shall be fitted with a 13A cordset

STANDARD FEATURES

- Designed for individual use or system installed with Turbofan E33T Convection Ovens
- 10 Half size sheet pan capacity
- 10 1/1GN / 12" x 20" steam pan capacity
- 2⁷/₈"/ 74mm tray spacing
- Compact 24"/ 610mm width
- Full viewing field reversible door
- 220-240V 13A plug-in cordset fitted
- 1600W cabinet heating
- Full double skin construction
- Touch Screen Control
- Individual shelf timers
- Electronic temperature control
- 600W heated humidification water tank
- Electronic humidity tank temperature control
- Autofill water tank system
- Continuous door seal
- Low velocity circulation fan system
- Dual LED halogen cabinet interior lamps
- 4 dia. 3"/76mm castors with 2 front castors with wheel and swivel lock, 2 rigid rear castors
- 100% recyclable packaging

ACCESSORIES - INCLUDED

- Two 5¾" / 145mm rear standoffs included
- 3M Cuno water filter kit complete with cartridge and connection fittings

ACCESSORIES - OPTIONAL

• 1/1 GN non-stick wire baskets



turbofan



EHT10-L

EHT10-L 1/1 GN Electric Humidified Holding Cabinet Touch Control

CONSTRUCTION

304 stainless steel interior cabinet Stainless steel front, sides and top exterior Stainless steel interior side racks Stainless steel frame, side hinged door 0.2"/5mm thick door glass Stainless steel control panel

Stainless steel control panel
Stainless steel base and rear panels

CONTROLS

5.7" LED backlit touch screen Individual shelf timers Temperature range 68-194°F / 20- 90°C

Humidity temp control

CLEANING

Stainless steel top and side exterior panels Removable plug-in door seal (no tools required)

SPECIFICATIONS

Electrical Requirements 220-240V, 50hz, 1-phase, 2.3kW, 9.6A 13A cordset fitted

Water Requirements

Cold water connection 3/4" BSP male 80psi / 550kpa maximum inlet pressure 22psi / 150kpa minimum inlet pressure

External Dimensions Width 24" / 610mm

Height 40" / 1015mm including dia. 3" / 76mm castors

Depth 26¾" / 680mm

321/2" / 825mm including Rear Standoffs

Nett Weight 194 lbs / 88kg Packing Data

269 lbs / 122kg 25 ft3 / 0.71m3 Width 27 ½" / 700mm

Height 46 ½" / 1170mm Depth 34" / 865mm

INSTALLATION CLEARANCES

Rear 53/4" / 145mm including Rear Standoffs

LH Side 0" / 0mm RH Side 1" / 25mm

CLEARANCE FROM SOURCES OF HEAT

A minimum distance of 12" / 300mm from the appliance

sides is required

OBLUE SERL

blue-seal.co.uk turbofanoven.com

United Kingdom Blue Seal Limited

Unit 67

Gravelly Business Park

Gravelly

Birmingham B24 8TQ

England


Telephone 0121-327 5575 Facsimile 0121-327 9711 sales@blue-seal.co.uk www.blue-seal.co.uk


Australia Moffat Pty Limited


740 Springvale Road Mulgrave, Victoria 3170 Australia Telephone 03-9518 3888 Facsimile 03-9518 3833 vsales@moffat.com.au www.moffat.com.au

New Zealand Moffat Limited

Christchurch
45 Illinois Drive
Izone Business Hub
Rolleston 7675
Telephone +64 3-983 6600
Facsimile +64 3-983 6660
sales@moffat.co.nz
www.moffat.co.nz









Designed and manufactured by

MOFFAT

ISO9001

All Turbofan products are designed and manufactured by Moffat using the internationally recognised ISO9001 quality management system, covering design, manufacture and final inspection, ensuring consistent high quality at all times.

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.



© Copyright Moffat Ltd 1688 UK.TFN.S.20.01

