



CSR-751
 CSN-751



CSR-1302
 CSN-1302

mod.	range °C	length (mm)	height (mm)	depth (mm)	shelves GN 2/1	capacity (L)	voltage	refrigerant	frig. power W	power W	CCE EEC 2015/1094 EN16825
CSR-751	-2°C +8°C	695	2115	730	3	505	230V-50Hz	R134a	245	253	E
CSN-751	-20°C -15°C	695	2115	730	3	505	230V-50Hz	R290	606	546	E
CSR-1302	-2°C +8°C	1390	2115	730	6+3	1201	230V-50Hz	R134a	485	442	F
CSN-1302	-20°C -15°C	1390	2115	730	6+3	1201	230V-50Hz	R290	907	883	F

we reserve the right to change specifications without prior notice

- AISI-430 stainless steel exterior, rear side in galvanized panel
- AISI-430 stainless steel interior, rounded corners and AISI-304 stamped bottom
- AISI-304 doors with self closing system, blocked opening, magnetic gasket and possibility of changing the opening sense
- Shelves made of plasticized steel wire, height adjustable
- Stainless steel adjustable legs, 125 to 200 mm
- Removable and fan assisted condenser unit
- Fan assisted evaporator, with epoxy anticorrosion coating.
- Automatic evaporation of defrost water
- 40 Kg/m³ density polyurethane insulation, zero ODP and GWP
- Digital temperature control, optimized defrost, high-temperature condensation alarms. Efficient management of energy consumption
- Operating temperature 38°C ambient

S-LINE

