



ICC202E - RATIONAL iCombi Classic - Model 20-2/1 - Electric Freestanding Combi Oven -67.9 kW The RATIONAL iCombi Classic 20-2/1 is truly multitalented, and will quickly become the indispensable assistant in your kitchen.

- Large 20 x GN 2/1 capacity, ideal for mass catering and for food service establishments with high output requirements
- Produce consistent high quality results with crisp crusts, attractive diamond grill patterns, or crispy breaded products
- Easy to use controls, with recognisable symbols and dial with a push function
- Digital display of cooking chamber humidity, time, and adjustable temperature

- Store up to 100 cooking programmes with as many as 12 steps
- Steam mode with steam regulation in 10% stages, together with consistent cooking cabinet temperature and optimal steam saturation, provides a uniform cooking process
- Advantages of steam combined with benefits of convection heat: short cooking time, reduction in shrinkage and intensive aromas with appetising colours. No cooking loss, no drying, high quality
- 4 automatic cleaning programmes, and integrated hand shower

Summary		Power and Performance	
Julillary		i ower and i errormance	
Brand	Lincat	Total Power kW	67.9
Range	RATIONAL	Temperature Range °C	30-300
Series	iCombi Classic	IP Rating	IPX5
Power Type	Electric	Temperature Control	Electronic
Jnit Type	Free-standing	Oven Rating kW	Steam connection = 54.0; Hot ai
Available in UK Only	Yes	o ron namng m	connection = 66.0
JK Warranty	RATIONAL 2 Years Parts and Labour		
,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	Warranty		
Key Specifications		Capacity	
VRAS Approved	Yes	Gastronorm Capacity	20 x GN2/1
ype of Lighting	LED	Portions per Day	300-500
Number of Grids included	0		
Weights and Dimensions		Supply Connections	
Jnit Height (External) mm	1872	Requires Installation	Yes
Jnit Width (External) mm	1082	Requires Electrical Supply	Yes
Jnit Depth (External) mm	1117	UK 3 Pin Plug	No
Net Weight Kg	304	Requires Hardwiring	Yes
		<b>Electrical Supply Rating Watts</b>	67,900
		Three Phase Amps	L1=100.0; L2=100.0; L3=100.0
		Three Phase Voltage	400
		Water Connection Pressure Bar	6
		Drain Connection	DN 50 mm
		Water Connection	3/4"





## **Shipping**

Packed Weight Kg 334.4 Packed Height cm 204.3 Packed Width cm 119 Packed Depth cm 121.8

## **Available Accessories**

60.70.464 RATIONAL Applicance Connection Kit - Model 6-1/1-20-2/1 - with Adapter for Model XS

6013.1103 RATIONAL Roasting and Baking Tray - Non-stick - GN1/1(325 x 530 mm)

6015.1103 RATIONAL Perforated Baking Tray - GN1/1(325 x530 mm)

6015.1165 RATIONAL Stainless Steel Perforated Container - GN1/1(325 x 530 mm) - 55 mm deep



**Lincat Limited** 

Whisby Road,

Lincoln, LN6 3QZ,

United Kingdom

**Company No:** 2175448

A member company of

**Customer Care** 

**Tel:** +44 1522 875500

Email: care@lincat.co.uk

**Export Customers** 

**Tel:** +44 1522 875536

Email: export@lincat.co.uk

**Opening Hours** 

Monday - Friday:

8.30am - 5pm