



- Power load: 1 kW | 230 V | 50 Hz
- Temperature range: 30 °C to 90 °C
- Control unit: Electronic
Toggle
- Protection class: IPX4
- Basin size, GN format: 2 x 1/1 GN
- Control lamp: Heat up
ON/OFF
- Temperature control: Stepless
Thermostatic
- Delivery state: Building kit (simple assembly)
- Swivel casters: 4 swivel casters, 2 with brake
- Depth GN container max.: 200 mm
- Heating type: Dry heated
- ON/OFF switch: Yes
- Thermostat: Yes
- Diameter casters: 125 mm
- Length cable: 3 m
- Connection cable type: Spiral cable
- Wheel buffer: 4 units, plastic
- Double-walled basin: Yes
- Not included in delivery: GN containers
- Material: CNS 18/10
- Important information: -
- Water drain tap: No
- Number of tanks: 1
- Heating zones can be controlled separately: No
- Size: W 650 x D 820 x H 855 mm
- Weight: 32 kg

Oil and grease remover F1L



- Designed for: Wipe-off work surfaces, stainless steel surfaces
Machines, appliances
Tiled walls and floors
Highly effective against deposits in coffee cans
- Model: Liquid
High concentrate
- Ph level: 13
- HACCP compliant: Yes
- Chlorine-free: Yes
- Phosphate-free: Yes
- Important information: Keep out of the reach of children!

Code-No. 173076
GTIN 4015613731896

Oil and grease remover F1L



- Content: 6 x 1 litre
- Model: Liquid
- HACCP compliant: Yes
- Chlorine-free: Yes
- Phosphate-free: Yes
- Including: -
- Order quantity unit: 1 box (6 bottles)
- Designed for: Wipe-off work surfaces, stainless steel surfaces
Tiled walls and floors
Highly effective against deposits in coffee cans
Machines, appliances

Code-No. 173276
GTIN 4015613761176