



**Green** Granite-Top Pizza Prep Counters  
**SPI-7-135-20-GR / SPI-7-180-30-GR / SPI-7-225-40-GR**



2 YEARS WARRANTY



2-3 DAY DELIVERY



UK SERVICE SUPPORT



MADE IN THE EU



**Specifications**

Model	Doors	Capacity Gross / Nett	Temperature	Energy Usage	Dimensions (mm) Width / Depth / Height	Energy Rating	Refrigerant
SPI-7-135-20-GR	2	290 ltrs / 143 ltrs	-2°C to +8°C	2.0 kW/hr	1342 / 700 / 1080	B	R290a
SPI-7-180-30-GR	3	452 ltrs / 214 ltrs	-2°C to +8°C	2.6 kW/hr	1792 / 700 / 1080	C	R290a
SPI-7-225-40-GR	4	615 ltrs / 285 ltrs	-2°C to +8°C	3.0 kW/hr	2242 / 700 / 1080	C	R290a

**Key Features**

- |                                       |                                    |
|---------------------------------------|------------------------------------|
| Power supply: 13 amp plug             | Automatic defrost                  |
| Castors fitted as standard            | Intelligent air-circulation system |
| Heavy-duty forced air system          | Drawer options available           |
| Stainless Steel interior and exterior | Heavy-duty granite work-top        |

## Green Pizza Prep Counters

**SPI-7-135-20-G / SPI-7-180-30-G / SPI-7-225-40-G**



2 YEARS  
WARRANTY



2-3 DAY  
DELIVERY



UK SERVICE  
SUPPORT



MADE IN  
THE EU

### Efficiency

- “Ventilation Gill” on the front panel keeping the cooling unit system ventilated and running more efficiently.
- Forced draft evaporator with anti-corrosion cover.
- Intelligent Air Circulation system ensures perfect temperature consistency with its innovative airflow design.
- 50 mm thickness, CFC-free, high-density (40 kg/m<sup>3</sup>) polyurethane insulation, injected under high pressure

### Features

- Fitted with foot pedal and castors. Height adjustable Stainless Steel legs available as an option (125mm - 200mm).
- Removable guiding rails enable more convenient cleaning operations without any additional tools. Placing and adjusting the wire grids at the desired height is possible without using extra rails. Epoxy-coated wire grids, to improve protection, allow storage of different packaging types and have a maximum loading capacity of up to 40 kg.
- Removable pull-out/push-in magnetic door gasket to keep maximum hygiene and maintain the insulating properties.
- Heavy-duty 30mm granite work top with side splash-back from 150mm to 250mm high and rear splash-back of 250mm high, preventing spillage behind the counter.
- Hinged doors with automatic return for a perfect closing that minimize temperature gain. Doors have a 120° dwell position and closes automatically at less than 90°. Door hinges are also reversible allowing the counter to be adapted on-site.
- Control panel and engine ventilation with pivoting front opening.
- Intuitive digital control allows temperature parameters to be adjusted easily and quickly.
- Luminous start-stop light button.
- Automatic evaporation of defrost water. Hot gas coming from the compressor is used to automatically evaporate defrost water, instead of by means of heating elements, achieving even less energy consumption and reducing in half defrost time.
- Equipped with 1 grid GN 1/1 per each door.
- Rounded edge interiors, easier cleaning operations to reduce potential dirt traps.

### Contact

**Website:** [www.sterlingpro.co.uk](http://www.sterlingpro.co.uk) / **Phone:** 01264 560190 / **Email:** [sales@sterlingpro.co.uk](mailto:sales@sterlingpro.co.uk)